

CP- UNR-4K2162-V2
16 Ch. Network Video Recorder



Main Features

- Support up to 1ch@8MP/4ch@1080P decoding
- Instastream/H.265/ H.264+ codec decoding
- Up to 8MP resolution preview and playback
- 160Mbps Incoming/ 160Mbps Outgoing bandwidth
- Support 2 SATA HDDs up to 10TB Each, 2 USB ports(2.0)
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UNR-4K2162-V2

16 Ch. Network Video Recorder

Feature

Processor
 Operating System
 IP Camera Input
 Two-way Talk
 User Interface
 Video Output
 Compression
 Encode Strategy
 Total Bandwidth
 Video Resolution
 Video Recording
 Video Display Split
 OSD
 Bit Rate
 Motion Detection
 Video Loss
 Camera Blank
 Smart Phone
 Hard Disk
 Trigger Events
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Interface Ports
 Record Interval
 Max User Account
 Ethernet

Specification

Dual-core embedded processor
 Embedded LINUX
 16 channel
 1 channel Input, 1 channel Output, RCA
 GUI
 1 HDMI, 1 VGA
 H.265, H.264+
 Instastream
 160Mbps Incoming/ 160Mbps Outgoing bandwidth
 1920×1080, 1280×1024, 1280×720, 1024×768
 8MP/6MP/5MP/4MP/3MP/1080P/ 720P/ D1&etc.
 1/4/8/9/16
 Camera title, Time, Camera lock, Motion detection, Recording
 16Kbps ~ 20Mbps Per Channel
 MD Zones: 396(22×18).
 Supports
 Supports
 iPhone, iPad, Android Phone
 2 SATA III ports, up to 10TB Each
 Recording, PTZ, Tour, Video Push, Snapshot, and Screen Tips
 Manual, Schedule (Regular (Continuous), MD, Stop
 Time/Date, MD & Exact search (accurate to second)
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
 USB Device / Network
 1 HDMI, 1 VGA, 2 USB Ports(1 Rear USB2.0, 1 Front USB2.0)
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 128 users
 1 RJ-45 port (10/100/1000Mbps)

CP- UNR-4K2162-V2
16 Ch. Network Video Recorder

Feature

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

HTTP/HTTPS, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, DNS, IP Filter, DDNS, IP Search, ONVIF 2.4, SDK, CGI

DC12V/4A

<3W (without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm x 281.5mm x 56mm

1.6kg (without HDD)