

2MP Fixed Dual Light Network Camera



SR-C2B-F4A-DL

KEY FEATURES

- High quality image with 2MP, 1/3" CMOS sensor
- 2MP(1920*1080)@30fps;720P (1280*720)@30fps
- Ultra 265, H.265, H.264
- 2D/3D DNR (Digital Noise Reduction)
- ROI (Region of Interest)
- ONVIF Conformance
- Smart IR, up to 30m (98ft) IR distance
- 3 Axis
- Built in Mic
- Wide temperature range: -30°C to 60°F (-22°C to 140°F)
- Support PoE power supply
- IP67



Camera	
Max Resolution	2 MP
Sensor	1/3.0" CMOS
Min. Illumination	Colour: 0.005Lux (F1.6, AGC ON) 0 Lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
Shutter	Auto/Manual, 1 to 1/100000 s
Adjustment Angle	Pan: 0 ~ 360, Tilt: 0 ~ 90, Rotate: 0 ~ 360
S/N	> 52 dB
WDR	DWDR
Lens	
Focal Length	4.0 mm
Iris	F1.6
Field of View (H)	67.3°
Field of View (V)	37.2°
Field of View (D)	77.8°
DORI	
DORI Distance (Lens)	4.0 mm
DORI Distance (Detect)	73.5m(241.0ft)
DORI Distance (Observe)	29.4m(96.4ft)
DORI Distance (Recognize)	14.7m(48.2ft)
DORI Distance (Identify)	7.3m(24.1ft)
Illuminator	
Supplemental Light	Dual light
Illumination Distance (IR)	30 m (98.4 ft)
Illumination Distance (Warm Light)	15 m (49.3 ft)
Wavelength	850 nm
IR On/Off Control	Auto/Manual
Video	
Video Compression	Ultra 265, H.265, H.264
H.264 Code Profile	Baseline profile, Main profile, High profile
Frame Rate	Main Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps; Sub Stream: 640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps
Video Bit Rate	128 Kbps to 6144 Kbps
U-code	Support
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 8 areas
Video Stream	Dual Streams

Image	
White Balance	Auto, Outdoor, Fine Tune, Sodium Lamp, Locked, Auto2
Digital Noise Reduction	2D/3D DNR
Smart IR	Support
Flip	Normal, Flip Vertical, Flip Horizontal, 180°
HLC	Support
Defog	Digital Defog
Event	
Basic Detection	Motion Detection, Audio Detection, Human Body Detection 2.0
General Function	Watermark, IP Address Filtering, Access Policy, ARP Protection, RTSP Authentication, User Authentication, HTTP Authentication
Audio	
Audio Compression	G.711U, G.711A
Audio Bitrate	64 Kbps
Suppression	Support
Sampling Rate	8 kHz
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, DNS, DDNS, NTP, UPnP, HTTP, SMTP, QoS, RTCP, RTMP
Compatible Integration	ONVIF (Profile S, Profile T), API, SDK
User/Host	Up to 32 users. 2 user levels: administrator and common user
Client	Uniarch Client, Uniarch app
Web Browser	Plug-in free live view: Chrome 57+, Firefox 58+, Edge 16+
Interface	
Built-in Mic	Support
Network	1 × RJ45 10 M/100 M Base-TX Ethernet
Certification	
EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035) FCC (FCC 47 CFR part15 B)
Safety	CE LVD (EN 62368-1)
Environment	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU)
Protection	IP67 (IEC 60529)
General	
Power	PoE (IEEE 802.3af) Power consumption: Max 3.5W
Dimensions	140 × 61 × 65mm (5.5" × 2.4" × 2.6")
Weight	0.15kg (0.34lb)
Material	Graphene + Plastic
Storage Environment	-30°C to 60°C (-22°F to 140°F), Humidity: ≤ 95% RH (non-condensing)
Working Environment	-30°C to 60°C (-22°F to 140°F), Humidity: ≤ 95% RH (non-condensing)
Surge Protection	4 KV
Web Client Language	English