





USB Type-C 5-in-1 Hub

Bridge Devices, Expand Connections

UH5020C




1× HDMI
4K@60Hz



1× PD
100W



1× USB-C
5 Gbps



2× USB-A
5 Gbps

Highlights



Plug & Play
For Various Operating Systems



Convenient & Stylish
Self-Storage for Connector

Bridge Devices, Expand Connections




HDMI

Ultra High-Definition
Media Display



PD 3.0

Powerful 100W
Fast Charging



USB 3.0

5 Gbps SuperSpeed
Data Transfer



Scratch Resistant

Aluminum Alloy Case



Durable Design

Braided Cable

Specifications

Hardware

- **Interface:**
 - 1× PD 100W Charging
 - 1× USB Type-C 5Gbps
 - 2× USB Type-A 5Gbps
 - 1× HDMI 4K@60Hz
- **Connector:**
 - 1× USB Type-C
- **PD Input:**
 - 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A
- **USB-C Connector Input:**
 - 5V/3A



For more information, please visit
https://www.tp-link.com/products/details/?model=UH5020C_V1
or scan the QR code left

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.
Specifications are subject to change without notice. Other brands and product names are trademarks or registered trademarks of their respective holders.
*Port transmission specifications are the testing results conducted by TP-Link laboratory. Actual transfer rate is not guaranteed and will vary as a result of device conditions and environmental factors.
©2025 TP-Link

Physical

- **Dimension (W×D×H):**
 - 4.26 × 1.57 × 0.48 in (108.2 × 40 × 12.2 mm)
- **Case:**
 - Aluminum Alloy Case
- **Cable:**
 - 180mm Braided Cable
- **Package Contents:**
 - 1× UH5020C
 - 1× Quick Installation Guide

Others

- **Supported Systems:**
 - Windows, iOS, macOS, iPadOS, Chrome OS, Linux, Android
- **Certification:** CE, FCC, RoHS, HDMI, BSMI
- **Environment:**
 - Operating Temperature: 0°C~40°C (32°F~104°F)
 - Operating Humidity: 10%~90% non-condensing
 - Storage Humidity: 5%~90% non-condensing